



TECHNICAL INFORMATION

Dimensions	470w x 517d x 760-790h
Rack Dimension	350 x 350 & 350 x 457
Clear Entry Height	311
Rinse Water Consumption	3.0L Per Cycle

WATER CONNECTIONS

Connection Point	3/4 inch (19mm)
Inlet Temperature	55c Max
Flow Rate	11 L/Min
Flow Pressure	0.5 bar minimum

ELECTRICAL

Single Phase	240v 1N - 15amp (TCL 3.18Kw)
--------------	------------------------------

GENERAL DATA

Weight (Net/Gross)	40Kg / 57Kg
Tank Capacity	10L
Noise Emission	70dB(A)
Cycle Times	1.5 & 2.0 Minute
Theoretical Capacity	960 glasses per hour

STANDARD INCLUSIONS

1x 15amp Plug and Lead
1x 1M Flexible Water Connection Hose
1x 1M Flexible Waste Hose
1x 350 x 350 Glass Rack

STANDARD FEATURES

- LCD control with digital temperature display
- Drain pump
- Rinse pump
- Integrated chemical pumps
- Dual filtration
- 'Air Gap' back flow prevention
- Insulated door
- Double skinned chamber
- Anti-block wash arms, lightweight and easy to remove for cleaning
- Made in UK
- Watermark approved